

Overlight dCSS Optical Receiver with 4 dCSS/Legacy+Terr. outputs + PSU (UK plug) For SKY applications, FM/DAB/UHF/SAT

Complete optical Wideband satellite and terrestrial receiver and power supply unit with UK plug. The receiver captures the TV optical signal on a single fiber (1200...1600nm) and restores the original terrestrial and satellite TV signals, providing 4 dCSS/Legacy + Terr. outputs.

Thanks to its optimized electronics and low losses, it is possible to reduce the number of amplifiers required and simplify deployment in collective installations, while preserving the signal quality throughout the process. Furthermore, it is fully indicated for use in GPON installations, and it perfectly adapts to SKY applications.

This device is part of the Overlight system, that distributes satellite and terrestrial signals to multiple users through a single optical fiber.

Ref.	237633
-------------	--------

EAN13	8424450319277
--------------	---------------

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	830.00 g
-------------------	----------

Gross weight	950.00 g
---------------------	----------

Width	149.00 mm
--------------	-----------

Height	130.00 mm
---------------	-----------

Depth	43.00 mm
--------------	----------

Main product weight	670.00 g
----------------------------	----------

Highlights

- Very compact in dimensions and weight
- Compatible with GPON deployments
- Supports SKY modes
- Low losses
- Optimized electronic behavior
- 100% European design, quality, and manufacturing
- SC/APC optical connector
- F-type RF connectors
- High-screening Zamak chassis
- Can be wall-mounted using screws

Application example

