

Overlight Quad Optical Receiver FM/DAB/UHF/SAT

This complete optical Wideband satellite and terrestrial receiver captures the TV optical signal on a single fiber (1200...1600nm) and restores the original terrestrial and satellite TV signals, providing 4 RF outputs with Quad mode: the four polarities and bands are provided on each connector.

Thanks to its optimized electronics and low losses, it allows to reduce the number of amplifiers required and simplifies deployment in the design of collective installations, preserving the signal quality throughout the process. Furthermore, it is fully indicated for use in GPON installations.

This device is part of the Overlight system, that distributes satellite and terrestrial signals to multiple users through a single optical fiber.

This product is certified with the European IRS Certification Scheme mark, representing that it has passed the relevant test as set out in the latest EICS test specification, available from the DTG or CAI.

Ref.	237650
-------------	--------

EAN13	8424450319291
--------------	---------------

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	840.00 g
-------------------	----------

Gross weight	960.00 g
---------------------	----------

Width	149.00 mm
--------------	-----------

Height	130.00 mm
---------------	-----------

Depth	43.00 mm
--------------	----------

Main product weight	670.00 g
----------------------------	----------

Highlights

- Very compact in dimensions and weight
- Compatible with GPON deployments
- Supports SKY modes
- Low losses
- Optimized electronic behavior
- 100% European design, quality, and manufacturing
- SC/APC optical connector
- F-type RF connectors
- High-screening Zamak chassis
- Can be wall-mounted using screws