

Technical Document
2 Fibre OS2 G.657.A2 Tight Buffered
Duplex MD 302 LSNH Black

webro

Part Number: 33000002005C-BLK-01

Description: 2 Fibre OS2 G.657.A2 Tight Buffered
Duplex MD 302 LSNH Black



Product Construction

Fibre Type	:	OS2, G.657.A2
Number of Fibre	:	2
Colour Code	:	Orange, Blue
Strength Members	:	High Tensile Aramid Yarn
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	Black

Mechanical Characteristics

Outer Jacket Thickness	:	0.4mm
Overall Diameter	:	2.8mm ± 0.1mm
Temperature Range	:	-5°C to +50°C to EN 60794-1-22-F1
Bend Radius	No Load :	15 x Overall Diameter to EN 60794-1-21-E11a
	Load :	20 x Overall Diameter to EN 60794-1-21-E11b
Weight	:	7.6 kg/km

Electrical Characteristics

Nominal Buffer Diameter	:	0.9mm
Maximum Tensile Strength	:	280N to EN 60794-1-21-E1
Maximum Crush Resistance	:	1000N to EN 60794-1-21-E3
Maximum Impact Resistance	:	5Nm to EN 60794-1-21-E4

Certifications & Standards

Flame Retardancy	:	BS EN 60332-3-22A
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
CE CPR Classification	:	Cca s1, d0, a1 to EN 50575:2014+A1:2016



Publication Date: 06/09/2024

Revision Number: 2.0

Written by: GB

Authorised by: GB

Technical Document
2 Fibre OS2 G.657.A2 Tight Buffered
Duplex MD 302 LSNH Brown

webro

Part Number: 3300000205C-BRN-01

Description: 2 Fibre OS2 G.657.A2 Tight Buffered
Duplex MD 302 LSNH Brown



Product Construction

Fibre Type	:	OS2, G.657.A2
Number of Fibre	:	2
Colour Code	:	Orange, Blue
Strength Members	:	High Tensile Aramid Yarn
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	Brown

Mechanical Characteristics

Outer Jacket Thickness	:	0.4mm
Overall Diameter	:	2.8mm ± 0.1mm
Temperature Range	:	-5°C to +50°C to EN 60794-1-22-F1
Bend Radius	No Load :	15 x Overall Diameter to EN 60794-1-21-E11a
	Load :	20 x Overall Diameter to EN 60794-1-21-E11b
Weight	:	7.6 kg/km

Electrical Characteristics

Nominal Buffer Diameter	:	0.9mm
Maximum Tensile Strength	:	280N to EN 60794-1-21-E1
Maximum Crush Resistance	:	1000N to EN 60794-1-21-E3
Maximum Impact Resistance	:	5Nm to EN 60794-1-21-E4

Certifications & Standards

Flame Retardancy	:	BS EN 60332-3-22A
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
CE CPR Classification	:	Cca s1, d0, a1 to EN 50575:2014+A1:2016



Publication Date: 06/09/2024

Revision Number: 2.0

Written by: GB

Authorised by: GB

Technical Document
2 Fibre OS2 G.657.A2 Tight Buffered
Duplex MD 302 LSNH White

webro

Part Number: 33000002005C-WHT-01

Description: 2 Fibre OS2 G.657.A2 Tight Buffered
Duplex MD 302 LSNH White



Product Construction

Fibre Type	:	OS2, G.657.A2
Number of Fibre	:	2
Colour Code	:	Orange, Blue
Strength Members	:	High Tensile Aramid Yarn
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	White

Mechanical Characteristics

Outer Jacket Thickness	:	0.4mm
Overall Diameter	:	2.8mm ± 0.1mm
Temperature Range	:	-5°C to +50°C to EN 60794-1-22-F1
Bend Radius	No Load :	15 x Overall Diameter to EN 60794-1-21-E11a
	Load :	20 x Overall Diameter to EN 60794-1-21-E11b
Weight	:	7.4 kg/km

Electrical Characteristics

Nominal Buffer Diameter	:	0.9mm
Maximum Tensile Strength	:	280N to EN 60794-1-21-E1
Maximum Crush Resistance	:	1000N to EN 60794-1-21-E3
Maximum Impact Resistance	:	5Nm to EN 60794-1-21-E4

Certifications & Standards

Flame Retardancy	:	BS EN 60332-3-22A
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
CE CPR Classification	:	Cca s1, d0, a1 to EN 50575:2014+A1:2016



Publication Date: 06/09/2024

Revision Number: 2.0

Written by: GB

Authorised by: GB