

Technical Document
Alternative to Belden 8723
2pair 22awg LSNH Grey

webro

Part Number: 428723C-LSNH-SLT

Description: Alternative to Belden 8723 2pair
22awg Individual Foil Screened Pairs LSNH Grey



Product Construction

Alternative to Belden	:	8723 NH
Conductor Material	:	Tinned Copper
Conductor Stranding	:	22awg; 7/0.25mm
Insulation Material	:	Low Smoke Non-Halogen (LSNH)
Number of Pairs	:	2
Core Colours	:	Black/Red, Green/White
Screening 1	:	Aluminium Foil Around Each Pair
Screening 1 Coverage	:	>100%
Drain Wire	:	Tinned Copper, 24awg Stranded
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	Grey



Mechanical Characteristics

Overall Diameter	:	4.3mm ± 0.20mm
Temperature Range	Fixed	-10°C to +70°C
	Flexing	+5°C to +40°C
Bend Radius	:	10 x Overall Diameter
Weight	:	33 kg/km

Electrical Characteristics

Conductor DC Resistance @20°C	:	≤ 50.10 Ω/km
Capacitance	Core to Core	90 pF/m ± 15
	Core to Screen	118 pF/m ± 25
Insulation Resistance @ 20°C	:	≥ 200 MΩ *M
Voltage Rating	:	50V

Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Cca s1a, d0, a1 to BS EN 50575:2014+A1:2016

Publication Date: 15/05/2024

Revision Number: 2.0

Written by: GB

Authorised by: GB