

Technical Document  
 WF125 75ohm Coax  
 Underground Green CAI Approved



Part Number: 600007F-GRN

Description: WF125 75ohm Coax Underground  
 HDPE Green - CAI Approved



**Product Construction**

Conductor Material	:	Plain Annealed Copper
Conductor Stranding	:	Solid, 1/1.25mm
Dielectric Material	:	Foam Polyethylene (FPE)
Dielectric Diameter	:	5.75mm ± 0.10
Screening 1	:	Overall Plain Copper Foil
Screening 1 Coverage	:	> 100%
Screening 2	:	Plain Copper Wire Braid
Screening 2 Coverage	:	> 60% ± 3
Sheath Material	:	High Density Polyethylene (HDPE)
Sheath Colour	:	Green



**Mechanical Characteristics**

Overall Diameter	:	8.0mm ± 0.3mm
Temperature Range	Fixed	-15°C to +70°C
	Flexing	-5°C to +70°C
Bend Radius	:	10 x Overall Diameter
Weight	:	70 kg/km

**Electrical Characteristics**

Inner Conductor DC Resistance	:	≤ 15.0 Ω/km @ 20°C
Outer Conductor DC Resistance	:	≤ 13.5 Ω /km @ 20°C
Characteristic Impedance	:	75 Ω ± 3
Nominal Capacitance	:	54 pF/m ± 3
Velocity of Propagation	:	82%

**Attenuation @20°C**

Frequency (MHz)	Attenuation (per 100m)	Frequency (MHz)	Attenuation (per 100m)
5	≤ 1.5 dB	860	≤ 15.5 dB
50	≤ 3.5 dB	1000	≤ 17.0 dB
100	≤ 5.0 dB	1750	≤ 22.0 dB
200	≤ 7.5 dB	2150	≤ 26.0 dB
460	≤ 11.5 dB		

**Return Loss @ 20°C**

Frequency (MHz)	Return Loss
5MHz - 470MHz	≥ 23 dB
470MHz - 862MHz	≥ 20 dB
862MHz - 2150MHz	≥ 18 dB

**Certifications & Standards**

CAI Certification	:	CAI 0142E
Screening Class	:	BS EN 50117
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Fca to BS EN 50575:2014+A1:2016



Publication Date: 04/07/2023

Revision Number: 2.0

Written by: GB

Authorised by: GB