



## 65WF25E

### 65" WINDOW FACING - HIGH BRIGHTNESS DISPLAY

Hisense Commercial Display solutions are perfect for high volume retail and corporate installation. A combination of seamless design and enhanced brightness ensure digital content vividly stands out from the crowd. Hisense window facing high brightness displays are perfect for the delivery of high-visibility and high-impact messaging to a target audience. With 2500 nits high brightness the 65WF25E is suitable for indoor environments with high levels of outdoor light.

#### Highlights



##### Round-the-clock operation

Designed with quad-core System on Chip (SoC) technology the window facing display can be used as reliable digital signage displays for both offline and cloud based content.



##### Landscape & portrait

Both landscape and portrait orientations are possible, providing you with endless creative and functional possibilities to fulfil your commercial or informative goals.



##### 2500 nits

With 2500 nits maximum brightness, the panels are 3500 well equipped to make your content vividly stand out in any commercial location. We also have 3500 and 4500 nit window facing displays available to special order. Please contact your Hisense representative for more details.



##### 178° Wide viewing angle

The extra wide 178° viewing angle is a perfect fit for shoppers, employees or visitors that will view Window Facing displays from diverse angles while passing by.



##### Visible With Polarized Sunglasses

2,500 nits LCD to give you a clear image, even in direct sunlight. Enables clear visibility even when the viewer is wearing polarized sunglasses.



##### Smart Brightness Sensor

Adjusts the brightness of the monitor automatically according to the surrounding lighting conditions. This feature considerably reduces power consumption and increases the monitor's lifetime.



## Specifications

### General

Special Order

Model	65WF25	65WF35	65WF45
Screen Size	65"	65"	65"
Screen Active Area(mm)	1428.48x803.52	1428.48x803.52	1428.48x803.52
Resolution	FHD(1920x1080)	FHD(1920x1080)	FHD(1920x1080)
Aspect Ratio	16:9	16:9	16:9
Brightness(nit)	2500nits	3500nits	4500nits
Contrast Ratio	4000:1	4000:1	4000:1
Dynamic CR	Upto 250000:1	Upto 350000:1	Upto 450000:1
Viewing Angle(H/V)	178°/178°	178°/178°	178°/178°
Backlight Life Cycle	50,000 Hrs	50,000 Hrs	50,000 Hrs
Operation Hours	24/7	24/7	24/7
Response Time	8ms	8ms	8ms
Screen Orientation	Portrait or Landscape	Portrait or Landscape	Portrait or Landscape

### System

OS	Android 9.0
CPU	ARM Quad Core Cortex-A53 1.5G
GPU	Arm Mali-G52 2EE MC1
DDR	DDR 2GB
ROM	16GB EMMC
Language	Chinese/English

### Connectivity

Input	USB2.0 x2, HDMI IN x2, Ethernet RJ45 x2, RS232 RJ45 x1, IR in x1, Sensor x1
Output	HDMI Out x1, Audio out x1

### Network connection

Wifi or LAN	Yes
3G/4G connection	Optional

### Speaker

Built in speaker	Yes
Line-out Support	Yes
BT Speaker Support	Yes

### Thermal management

Smart Backlight Control	Yes
Smart Temperature Control	Yes
Smart Fans Control	Fanless
Smart Monitoring System Cloud	Optional / CetusMSC
Overheating protection	Yes

### Power

Power Supply	AC 110 /220V,50/60Hz
Power Type	Built-In Power
Power Consumption	500W(Max.)

### Physical

IP rating	IP5X (Front Panel)
Glass	No
Shell	Aluminum
Standard Color	Black
Bezel width(T/L/R/B)	10mm(T/B/L/R)
Dimensions	1450.88(H)x826.22(W)x56.75(D) mm
Net Weight	30.2 kg
Packing Dimensions(W×H×D)	1611(W)x978(H)x180(D) mm
VESA	400 x 400mm
20GP container capacity (pcs)	72 PCS
40GP container capacity (pcs)	168 PCS

### Operation

Working environment	Indoor window facing
Auto Brightness control	Light sensor
Noise(Operating at 25±2 °C, 100cm apart from the module)	/
Operation Temperature (ambient temp.)	-10°C to 35°C (Direct Sunlight) -10°C to 45°C (w/o Direct Sunlight)
Operation Humidity	10% to 80%
Storage Temperature	-10°C to +60°C
Storage Humidity	10% to 80%

### What's in the box

Accessories	Power cord
	IR Receiver
	Remote Control
	AAA Batteries x 2
	WiFi Antenna
	Lifting Ring (M6) x 2
	Filler Pad (M6) x 2
	Spring Pad (M6) x 2
User Manual (Electronic Version)	

### Dimensions

65" | 1450.88 x 826.22 x 56.75 mm  
30.2 kg

