

PRE-WIRED BEAM TOWERS

	2 Beams	3 Beams
Single-sided (180°)	TAS-2PW	TAS-2PW3
Double-sided (360°)	TAD-2PW	TAD-2PW3

FEATURES

- Available in 2m height
- Pre-wired and ready to install
- Reduced time on site
- Includes heaters, thermostat & tamper switch
- Compatible with KH series Beams

2M SINGLE OR DOUBLE-SIDED BEAM TOWERS PRE-WIRED AND INSTALLED WITH HEATERS, THERMOSTAT, TAMPER SWITCH & MOUNTING BRACKETS FOR 2 OR 3 BEAM UNITS PER SIDE.

Simply mount your chosen KH series beams and align to create robust perimeter intruder systems with ease, reducing installation time and labour costs on site.



INCLUDED

REQUIRED

OPTIONAL



ACCESSORY

ACCESSORY

ACCESSORY

QUAD BEAMS

ACCESSORY

ACCESSORY

ACCESSORY

HEATERS

For uninterrupted operation throughout the winter months.

MOTHERBOARD

With wiring terminals, function switches and thermostat.

TAMPER

Tamper switch to signal the removal of the Tower top.

PB-HFA-KH

Our market-leading HFA series optimised for Beam Towers.

TAPS

Anti-Climb Tamper Switch for high security applications.

TAFB

First-fix Floor Bracket provides anchor points for mounting.

TAPSU-2A

12VDC 2A In-Tower PSU (UK & Europe only).

SPECIFICATIONS

Model	TAS-2PW	TAS-2PW3	TAD-2PW	TAD-2PW3
Tower height	2m			
Field of view	180°		360°	
Supply voltage	12VDC			
Tamper output	Real time output (N.C.) · when the lid is removed from the tower			
Current consumption	1,020mA	1,530mA	2,040mA	3,060mA

