

## Surface Magnetic Contact

*Code: SC570/GY/G2/EN*

SC570 | Surface Contact | Grade 2 | Anthracite Grey | Non-resistored



This magnetic door contact can be used in most security systems up to and including grade 2 and environmental class II as specified in EN50131-1 and is certified to EN50131-2-6 by Kiwa FSS. This contact can be used on windows and doors to detect the unauthorised entry of an intruder. The contact is also protected against tampering with optional detection of removal from its mounting surface.

### Features & Benefits

- 6 Terminals
- Cover and wall tamper
- Available in white, brown or anthracite grey
- EN50131-2-6 Grade 2
- Environmental Class II



## Product Information

**Connection type** Wired

## Security

**EN50131-2-6 Grade** 2

**Tamper Protection** Cover & RFMS

## Environmental

**EN50130-5 class** Class II

**IP Rating** 3X

**Temperature range** -15°C - +40°C

## Housing

**Colour** Anthracite Grey

**Material** HIPS

**Contact Dimensions (mm)** 85 x 25 x 21

**Magnet Dimensions (mm)** 85 x 25 x 21

## Electrical

**Connection type** Wired

**No. of terminals** 6 Terminal

**Contact type** Normally Closed

**Contact Material** Rhodium

## Features

**Mode of operation** DP

**Operation Axes (X, Y, Z)** X, Y

**Pull-in gap (X, Y, Z)mm** 36, 27

**Suitable for Double Door** Yes

**No. of terminals** 6 Terminal