

Surface Magnetic Contact

Code: SC570/WH/G2/EN

SC570 | Surface Contact | Grade 2 | White | Non-resistored



This magnetic door contact can be used in most security systems up to and including grade 2 and environmental class II as specified in EN50131-1 and is certified to EN50131-2-6 by Kiwa FSS. This contact can be used on windows and doors to detect the unauthorised entry of an intruder. The contact is also protected against tampering with optional detection of removal from its mounting surface.

Features & Benefits

- 6 Terminals
- Cover and wall tamper
- Available in white, brown or anthracite grey
- EN50131-2-6 Grade 2
- Environmental Class II



Product Information

Connection type Wired

Security

EN50131-2-6 Grade 2

Tamper Protection Cover & RFMS

Environmental

EN50130-5 class Class II

IP Rating 3X

Temperature range -15°C - +40°C

Housing

Colour White

Material HIPS

Contact Dimensions (mm) 85 x 25 x 21

Magnet Dimensions (mm) 85 x 25 x 21

Electrical

Connection type Wired

No. of terminals 6 Terminal

Contact type Normally Closed

Contact Material Rhodium

Features

Mode of operation DP

Operation Axes (X, Y, Z) X, Y

Pull-in gap (X, Y, Z)mm 36, 27

Suitable for Double Door Yes

No. of terminals 6 Terminal