

# OEI-372S-H-W Indoor Station

## OEI-372S-H-W



### Overview

OEI-372S-H-W indoor station is one of the terminals in the digital building intercom system, with functions of video intercom, security alarm, network camera monitoring, etc., providing a safe and comfortable living environment for residents. It can be widely used in building systems such as smart communities, villas, and office parks.

### Features

- Rugged ABS casing and glass panel.
- 1024\*600 HD touch screen.
- Batch configuration transfer.
- Remote opening of linked door stations, one-key opening.
- Network camera monitoring, security alarm.

### Specifications

Model	OEI-372S-H-W
Hardware Specification	
Power Supply	DC12V±25%,IEEE802.3af, Standard PoE
Power Consumption	<10W

Screen	7-inch ultra-thin TFT LCD screen
Screen Resolution	Screen resolution 1024×600
Operation System	Linux
Audio Quality	Noise suppression, echo cancellation and AGC
Audio Input	1 built-in omnidirectional microphone
Audio Output	1 built-in speaker
Audio Compression Standard	MP3 G711
Audio Compression Bitrate	128Kbps
Interface	Power*1, network*1, Wi-Fi*1, RS485*1, IO output*2, IO input*8, TF card slot*1
Network	100Mbps network port, supports IEEE802.3af PoE power supply
Weight	360g
Dimensions (L x W x H)	193mm×143mm×25mm
Operating Environment	-10°C to +55°C, 10% to 90%, non-condensing, indoor
<b>Basic Business</b>	
Protocol	UNV private protocol

## Ordering Info

Product Model	Description
OEI-372S-H-W	Wall Mounted 7-Inch Indoor Station(Touch Screen)

## Dimensions

