




Series F Whyte Fibre Optic Splice Protectors

WSP-100-45 | WSP-100-60



-  Clear Outer Tube (shrink tube)
-  Clear Inner Tube (Fibre Tube)
-  Strength Member (stainless-steel pin)



45mm x 100



60mm x 100

These products are made up of cross-linked polyolefin heat-shrinkable tubes, hot melt tubes and a stainless-steel needle. It is specifically designed for the protection of fibre optical fusion splices. Available in either 60mm or 40mm lengths in bags of 100.

DESCRIPTION	WSP-100-45	WSP-100-60
Length of Tube (mm)	45	60
Inner Tube Diameter (mm)	2.2	2.2
After Recovery Diameter (mm)	3	3
Tensile Strength (Mpa)	18	18
Elongation at Break (%)	700	700
Material Density (g/m ³)	0.94	0.94
Dielectric Strength (kV/mm)	25	25
Minimum Shrink Temperature (°C)	120	120
Outer Tube Diameter (mm)	4.3	4.3
Stainless Steel Needle Diameter (mm)	1.5	1.5
Working Temperature (°C)	-55 to 100	-55 to 100
Dielectric Constant	2.5	2.5
Longitudinal Change (%)	±5	±5
Eccentricity	105	105
Volume Resistance Ω	1015	1015
Minimum Full Recovery Temperature (°C)	100	100